



321, 11979 – 40th Street SE, Calgary, AB, Canada T2Z 4M3

tel: 403.243.9728    fx: 403.243.9749    tf: 866.652.2339

## FIRE CADDY™ Product Specifications

### FIRE CADDY™ GH5501

	Honda Engine
Horsepower	5.5
Displacement (cc / cu. in.)	163 / 9.9
Bore (in.)	2.7
Stroke (in.)	1.8
Weight (lbs.)	33.1
Oil Fill Capacity (oz.)	21
Valve	overhead
Cylinders	aluminum
Air Cleaner	paper
Ignition	Transistorized Magneto
Lubrication	splash

### System and Pump

Suction Hose	20 feet of 3" non-collapsible
Discharge Hose	50 feet of ¾" high pressure rubber
Nozzle	Scotty air induction foam
Flow Rate @ full open nozzle	12 US gallons per minute @ 65 PSI
Free-Flow (2" secondary discharge)	100 US gallons per minute
Pressure Gauge	100 PSI liquid filled
Fire Suppressant Selector	0% to 6% @ 12 US gallons per minute, 65 PSI
Wheels	Solid Rubber
Hose Reel (for Discharge Hose)	Holds 50 feet of ¾" high pressure rubber, <i>or</i> 100 feet of 1" lay flat high pressure hose
Fire Suppressant	5 US gallons in integral tray
Weight (empty)	150 lbs
Weight (full w/ Fire Suppressant & motor fluids)	190 lbs
Dimension (Depth x Width x Height)	31" x 23" x 45" 79cm x 58cm x 114cm
Frame	Powder Coated Steel construction