



FIRE CADDY™ Product Specifications

FIRE CADDY™ GH5501

	Honda Engine
Horsepower	5.5
Displacement (cc / cu. in.)	163 / 9.9
Bore (in.)	2.7
Stroke (in.)	1.8
Weight (lbs.)	33.1
Oil Fill Capacity (oz.)	21
Valve	overhead
Cylinders	aluminum
Air Cleaner	paper
Ignition	Transistorized Magneto
Lubrication	splash

System and Pump

Suction Hose	20 feet of 3" non-collapsible
Discharge Hose	50 feet of ¾" high pressure rubber
Nozzle	Scotty air induction foam
Flow Rate @ full open nozzle	12 US gallons per minute @ 65 PSI
Free-Flow (2" secondary discharge)	100 US gallons per minute
Pressure Gauge	100 PSI liquid filled
Fire Suppressant Selector	0% to 6% @ 12 US gallons per minute, 65 PSI
Wheels	Solid Rubber
Hose Reel (for Discharge Hose)	Holds 50 feet of ¾" high pressure rubber, <i>or</i> 100 feet of 1" lay flat high pressure hose
Fire Suppressant	5 US gallons in integral tray
Weight (empty)	150 lbs
Weight (full w/ Fire Suppressant & motor fluids)	190 lbs
Dimension (Depth x Width x Height)	31" x 23" x 45" 79cm x 58cm x 114cm
Frame	Powder Coated Steel construction



FIRE CADDY™ OffRoad1125 - Custom Trailer for a FireCaddy c/w 125 US ga. tank

Dimensions: w/o FireCaddy / with FireCaddy	117”L x 44”W x 50”H / 117”L x 44”W x 64”H
Weight: trailer / trailer w/ water & full Fire Caddy)	280 lbs (130 kg) / 1690 lbs (770 kg)
Tongue Weight (empty or full)	100 lbs (45kg)
Frame	Powder Coated Steel Construction
Axle	2000 lb single axle
Suspension	Leaf Spring
Tires	5.30 x 12” tubeless
Water Tank	125 US Gallon Rated Capacity 1½” Discharge Bulkhead 12” Man Wing 3” Vented Cap
Included Accessories	2” trailer coupler Tongue Jack Safety Chain Integral Fire Caddy Mating Brackets

Notes: The 125 Gallon Fire Caddy Trailer is not rated for highway use and should only be used in off-road applications.

FIRE CADDY™ Trail1250 - Custom Trailer for a FireCaddy c/w 250 US ga. tank

Dimensions: w/o FireCaddy / with FireCaddy	8 feet long
Weight: trailer / trailer w/ water & full Fire Caddy)	
Tongue Weight (empty or full)	
Frame	Powder Coated Steel Construction
Axle	3500 lb Single Axle
Suspension	Double Eye
Tires	ST205/75R15
Wheels	White Spoke Rims Chrome Center Caps
Water Tank	250 US Gallon Rated Capacity 1½” Discharge Bulkhead 12” Man Wing 3” Vented Cap
Included Accessories	2” Molded Trailer Coupler Top Crank Jack Safety Chains & Hooks Integral Fire Caddy Mating Brackets Fold Down Endgag c/w Latches